

HIP (Hydrim Cleaning Solution with Instrument Protection) SciCan Ltd

Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) and WHIMS 2015 requirements

Issue Date: **16/10/2024**Print Date: **16/10/2024**S.GHS.USA.CAN.EN

SECTION 1 Identification

Product Identifier

Product name	HIP (Hydrim Cleaning Solution with Instrument Protection)	
Synonyms	Not Available	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses	Cleaner for Hydrim automatic instrument processor machines.
--------------------------	---

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	SciCan Ltd.
Address	1440 Don Mills Road Toronto Ontario M3B 3P9 Canada
Telephone	+1 416 445 1600
Fax	+1 416 445 2727
Website	https://www.scican.com/
Email	customerservice@scican.com

Emergency phone number

Association / Organization	InfoTrac	
Emergency telephone numbers	1-800-535-5053	
Other emergency telephone numbers	Not Available	

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Classification Serious Eye Damage/Eye Irritation Category 2, Acute toxicity (oral) Category 4

Label elements

Hazard pictogram(s)



Signal word

Warning

Version No: **1.1** Page **2** of **12** Issue Date: **16/10/2024**

Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

Hazard statement(s)

H302	Harmful if swallowed.
H319	Causes serious eye irritation.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P264	Wash hands thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P280	Wear eye protection.	

Precautionary statement(s) Response

P301+P312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.	
P330	Rinse mouth.	
P305+P351+ P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statement(s) Storage

Not applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local or regional regulations.
------	---

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
14860-53-8	5-10	tetrapotassium 1-hydroxyethylidene diphosphonate
1300-72-7	5-10	sodium xylenesulfonate
2687-94-7	1-5	1-octyl-2-pyrrolidone

SECTION 4 First aid measures

Description of first aid measures

Eye Contact

If this product comes in contact with the eyes:

Immediately hold eyelids apart and flush the eye continuously with running water.

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention if irritation develops or persists.

 Version No: 0.1
 Page 3 of 12
 Issue Date: 16/10/2024

 Print Date: 16/10/2024
 Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

	If skin or hair contact occurs:
Skin Contact	▶ Wash skin and hair with running water.
Inhalation	▶ No specific first aid measures are required.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully.
	 Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

Special protective equipment and precautions for fire-fighters

· · · · · · · · · · · · · · · · · · ·	
	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.
Fire Fighting	 Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area.
	► Avoid spraying water onto liquid pools.
	▶ DO NOT approach containers suspected to be hot.
	▶ Cool fire exposed containers with water spray from a protected location.
	▶ If safe to do so, remove containers from path of fire.
	Combustible. Slight fire hazard when exposed to heat or flame.
Fire/Explosion Hazard	 Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit irritating/ toxic fumes.
	▶ May emit acrid smoke.
	▶ Mists containing combustible materials may be explosive.
	May emit poisonous fumes.
	May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

 Version No: 0.1
 Page 4 of 12
 Issue Date: 16/10/2024

 Print Date: 16/10/2024
 Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handli	ng
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
	▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks.
	► Observe manufacturer's storage and handling recommendations contained within this SDS.

 Version No: 0.1
 Page 5 of 12
 Issue Date: 16/10/2024

 Print Date: 16/10/2024
 Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

Conditions for safe storage, including any incompatibilities

Suitable container	 Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Emergency Limits

Ingredient	Original IDLH	Revised IDLH
tetrapotassium 1- hydroxyethylidene diphosphonate	Not Available	Not Available
sodium xylenesulfonate	Not Available	Not Available
1-octyl-2-pyrrolidone	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
tetrapotassium 1- hydroxyethylidene diphosphonate	Е	≤ 0.01 mg/m³
sodium xylenesulfonate	E	≤ 0.01 mg/m³
1-octyl-2-pyrrolidone	С	> 1 to ≤ 10 parts per million (ppm)
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

8.2.1. Appropriate engineering controls

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Version No: 0.1 Page 6 of 12 Issue Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

Print Date: 16/10/2024

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

8.2.2. Individual protection measures, such as personal protective equipment



Eye and face protection

- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

Hands/feet protection

- ▶ Not normally required.
- **Body protection**
- Not normally required.
- Other protection
- Eye wash unit.

Not Available

Respiratory protection

Not normally required.

SECTION 9 Physical and chemical properties

Appearance

Information on basic physical and chemical properties

Physical state	Liquid	Relative density (Water = 1)	1.113
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	9.3-9.8	Decomposition temperature (°C)	Not Available
Melting point / freezing	Not Available	Viscosity (cSt)	Not Available
point (°C)			

 Version No: 0.1
 Page 7 of 12
 Issue Date: 16/10/2024

 Print Date: 16/10/2024
 Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>93.3	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidizing properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerization will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of anionic surfactants may produce diarrhea, bloated stomach, and occasional vomiting.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Anionic surfactants can cause skin redness and pain, as well as a rash. Cracking, scaling and blistering can occur. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. Direct eye contact with some anionic surfactants in high concentration can cause severe damage to the cornea. Low concentrations can cause discomfort, excess blood flow, and corneal clouding and swelling. Recovery may take several days.
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Although the salt of the organophosphate has not been tested, animal testing on the free acid aminotris(methylenephosphonic) acid revealed loss in body weight and changes in the weight of the liver, spleen

Version No: **0.1** Page **8** of **12** Issue Date: **16/10/2024**

HIP (Hydrim Cleaning Solution with Instrument Protection)

Print Date: 16/10/2024

and kidney.

HIP (Hydrim Cleaning
Solution with Instrument
Protection)

TOXICITY	IRRITATION
Inhalation LC50: > 20 mg/L	Not available
Oral LD50: >500 mg/kg	Not available
Dermal LD50: >5000 mg/kg	Not available

tetrapotassium 1-hydroxyethylidene diphosphonate

TOXICITY	IRRITATION
Oral (Rat) LD50: 520 mg/kg ^[2]	Not Available

sodium xvlenesulfonate

TOXICITY	IRRITATION
Oral (Rat) LD50: >10 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]
	Skin: no adverse effect observed (not irritating) ^[1]

1-octyl-2-pyrrolidone

TOXICITY	IRRITATION	
Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]	
Oral (Rat) LD50: 2050 mg/kg ^[1]	Skin: adverse effect observed (corrosive) ^[1]	

Leaend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

tetrapotassium 1hydroxyethylidene diphosphonate

For ATMP (aminotris(methylenephosphonic acid)) and its salts:

ATMP acid, the monosodium salt and hexasodium salts cause serious eye irritation, while the disodium to pentasodium salts do not cause eye irritation. The low pH would predict that ATMP acid should be severely irritant or corrosive to skin as well as eyes. Acute toxicity: In animals, ATMP has low acute toxicity.

Sensitization: Based on animal data and human exposure reports, ATMP is not classified with respect to skin sensitization. Toxicity after repeated exposure: Not classified.

Genetic toxicity / mutation-causing potential: ATMP and its salts do not cause genetic toxicity or mutations.

Cancer-causing potential: ATMP sodium salts and the acid are not expected to cause cancer.

Reproductive toxicity: Based on animal testing, ATMP and its salts do not cause reproductive toxicity.

For alkyl sulfates; alkane sulfonates and alpha-olefin sulfonates

Most chemicals of this category are not defined substances, but mixtures of homologues with different alkyl side chains. Common physical and/or biological pathways result in structurally similar breakdown products, and are, together with the surfactant properties, responsible for similar environmental behavior and essentially identical hazard profiles with regard to human health.

Acute toxicity: These substances are well absorbed after ingestion; penetration through the skin is however, poor. After absorption, these chemicals are distributed mainly to the liver.

In animals, signs of poisoning by mouth include lethargy, hair standing up, decreased motor activity and breathing rate, and diarrhea. Poisoning from skin contact caused irritation, tremor, tonic-clonic convulsions, breathing failure, and weight loss. The C-12-akyl sulfate sodium salt caused the greatest effect.

sodium xylenesulfonate

In eye irritation tests, C-12 containing alkyl sulfates at greater than 10% concentration were severely irritating and produced irreversible effects on the cornea. With increasing alkyl chain length, the irritating potential decreases, and the longer species are only mildly irritant.

Animal studies have not shown alkyl sulfates and C14-18 alpha-olefin sulfonates to cause skin sensitization. However there is anecdotal evidence to suggest sodium lauryl sulfate causes sensitization of the lung, resulting in hyperactive airway dysfunction and lung allergy, accompanied by fatigue, malaise and aching. Significant symptoms of exposure can persist for more than two years, and can be activated by a variety of non-specific environmental stimuli, such as exhaust, perfumes and passive smoking. Airborne sulfonates may be responsible for respiratory allergies, and in some cases, minor skin allergies. Repeated skin contact with some sulfonated surfactants has produced skin inflammation was sensitization in predisposed individuals.

Repeat dose toxicity: The liver seems to be the only organ that is affected by repeated exposure, with elevated levels of liver enzymes, an increase in liver weight and enlargement of liver cells being seen.

Genetic toxicity: Alkyl sulfates and alkyl-olefin sulfonates do not appear to cause mutations or genetic toxicity.

Cancer-causing potential: Animal testing suggested that alkyl sulfates and alpha-olefin sulfonates do not have cancer-causing potential.

Reproductive toxicity: In animal testing, these substances only caused harm to the fetus and/or offspring at levels which were toxic to the mother.

Developmental toxicity: Alkane sulfonates are not considered to be toxic to development.

Toxicological data is available and well documented for representative toluene, xylene and cumene sulfonates (including sodium, potassium, ammonium and calcium salts). These data show that hydrotropes have low toxicity for all routes, do not cause genetic damage, show no evidence of causing cancer in long-term skin studies, and have not caused birth defects, developmental defects or reduced fertility.

Version No: **0.1** Page **9** of **12** Issue Date: **16/10/2024**

HIP (Hydrim Cleaning Solution with Instrument Protection)

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

Acute Toxicity	~	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	×
Respiratory or Skin sensitization	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: X − Data either not available or does not fill the criteria for classification

Print Date: 16/10/2024

✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

(Hydrim Cleaning Solution with Instrument Protection)	Endpoint	Test Duration (hr)	s	pecies	Value	Sou	ırce
	Not Available	Not Available		ot Available	Not Available	Not	Available
	Trott/trailable	11017114114210	.	017114114010	Trot/trailable	1100	7.174.142.10
tetrapotassium	Endpoint	Test Duration (hr)	s	pecies	Value	Sou	ırce
1-hydroxyethylidene diphosphonate	Not Available	Not Available	N	ot Available	Not Available	Not	Available
sodium xylenesulfonate	F. 1	T. (2)				W.L.	
	Endpoint	Test Duration (hr)	Specie	s		Value	Source
	EC50	72h	Algae	or other aquatic pl	ants	~252mg/l	2
	EC50	48h	Crusta	cea		>400mg/l	1
	NOEC(ECx)	72h	Algae	or other aquatic pl	ants	40mg/l	2
	EC50	96h	Algae	or other aquatic pl	ants	>=230mg/l	2
1-octyl-2-pyrrolidone							
	Endpoint	Test Duration (hr)	Specie	s		Value	Source
	NOEC(ECx)	840h	Fish			0.91mg/l	2
	LC50	96h	Fish			~17.8mg/l	2
	EC50	72h	Algae	or other aquatic pl	ants	9.27mg/l	2
	EC50	96h	Algae	or other aquatic pl	ants	6.2mg/l	2
	EC50	48h	Crustad	cea		7.59mg/l	2

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1-octyl-2-pyrrolidone	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
1-octyl-2-pyrrolidone	LOW (LogKOW = 3.3314)

Mobility in soil

Ingredient	Mobility
1-octyl-2-pyrrolidone	LOW (Log KOC = 1593)

 Version No: 0.1
 Page 10 of 12
 Issue Date: 16/10/2024

 Print Date: 16/10/2024
 Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

SECTION 13 Disposal considerations

Waste treatment methods

• Containers may still present a chemical hazard/ danger when empty.

- Return to supplier for reuse/ recycling if possible.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Product / Packaging disposal
- ▶ Reduction
- Reuse
- Recycling
- ▶ Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means.

• Recycle containers if possible, or dispose of in an authorized landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
tetrapotassium 1-hydroxyethylidene diphosphonate	Not Available
sodium xylenesulfonate	Not Available
1-octyl-2-pyrrolidone	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
tetrapotassium 1-hydroxyethylidene diphosphonate	Not Available
sodium xylenesulfonate	Not Available
1-octyl-2-pyrrolidone	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

tetrapotassium 1-hydroxyethylidene diphosphonate is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Canada Non-Domestic Substances List (NDSL)

Version No: **0.1** Page **11** of **12** Issue Date: **16/10/2024**

Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

sodium xylenesulfonate is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

1-octyl-2-pyrrolidone is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Canada Domestic Substances List (DSL)

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	Yes
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)

None Reported

Additional Federal Regulatory Information

Not Applicable

State Regulations

US. California Proposition 65

None Reported

 Version No: 0.1
 Page 12 of 12
 Issue Date: 16/10/2024

 Print Date: 16/10/2024
 Print Date: 16/10/2024

HIP (Hydrim Cleaning Solution with Instrument Protection)

Additional State Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	No (tetrapotassium 1-hydroxyethylidene diphosphonate)
Canada - NDSL	No (sodium xylenesulfonate; 1-octyl-2-pyrrolidone; alcohols C12-14 ethoxylated propoxylated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (alcohols C12-14 ethoxylated propoxylated)
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (tetrapotassium 1-hydroxyethylidene diphosphonate; 1-octyl-2-pyrrolidone; alcohols C12-14 ethoxylated propoxylated)
Vietnam - NCI	Yes
Russia - FBEPH	No (tetrapotassium 1-hydroxyethylidene diphosphonate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	16/10/2024
Initial Date	09/11/2015

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.